



DHCPKit

DHCPKit Documentation

Release 1.0.0

S.J.M. Steffann

Apr 29, 2021

Contents

1	Distribution status	3
2	Documentation	5
2.1	IPv6 Server extension configuration	5
2.2	dhcpkit_kafka package	6
2.3	Changes per version	10
2.4	Applicable copyright licences	11
	Python Module Index	13
	Index	15

This package contains extensions to DHCPKit for sending detailed information about each processed DHCPv6 transaction to Kafka. This can be used to implement a looking glass and other monitoring tools.

CHAPTER 1

Distribution status

1 2 3 4 5

¹ https://pypi.python.org/pypi/dhcpkit_kafka

² https://pypi.python.org/pypi/dhcpkit_kafka

³ https://pypi.python.org/pypi/dhcpkit_kafka

⁴ https://pypi.python.org/pypi/dhcpkit_kafka

⁵ https://pypi.python.org/pypi/dhcpkit_kafka

CHAPTER 2

Documentation

2.1 IPv6 Server extension configuration

This is a server extension that publishes information on what the DHCPv6 server is doing to Kafka. You can then run a collector that collects the information from all the DHCPv6 servers and presents them on a single dashboard.

2.1.1 Overview of section types

Handlers

Configuration sections that specify a handler. Handlers process requests, build the response etc. Some of them add information options to the response, others look up the client in a CSV file and assign addresses and prefixes, and others can abort the processing and tell the server not to answer at all.

You can make the server do whatever you want by configuring the appropriate handlers.

Send-to-kafka

This section specifies the Kafka server cluster that data should be sent to.

Example

```
<send-to-kafka>
    broker host1:9092
    broker host2:9092

    topic dhcpkit.messages
</send-to-kafka>
```

Section parameters

server-name The name of this DHCPv6 server to label Kafka messages with

Default: The FQDN of the server

source-address The source address to use when connecting to Kafka

Example: “dhcp01.example.com”

topic The Kafka topic to publish DHCPKit messages on

Default: “dhcpkit.messages”

broker (multiple allowed) Kafka broker to connect to

Default: “localhost:9092”

2.2 dhcpkit_kafka package

Basic information about this package

2.2.1 Subpackages

dhcpkit_kafka.server_extension package

This handler provides a looking glass into DHCP server operations by sending interesting information on Kafka

```
class dhcpkit_kafka.server_extension.KafkaHandler(source_address: Tuple[str, int],  
                                                 brokers: Iterable[Tuple[str,  
                                                 int]], topic_name: str;  
                                                 server_name: str)
```

Bases: dhcpkit.ipv6.server.handlers.Handler

Option handler that provides a looking glass into DHCP server operations by logging information about requests and responses into an SQLite database.

The primary key is (duid, interface_id, remote_id)

```
analyse_post (bundle: dhcpkit.ipv6.server.transaction_bundle.TransactionBundle)
```

Finish the Kafka message and send it.

Parameters **bundle** – The transaction bundle

```
analyse_pre (bundle: dhcpkit.ipv6.server.transaction_bundle.TransactionBundle)
```

Start building the Kafka message.

Parameters **bundle** – The transaction bundle

```
connect ()
```

Connect the producer to the broker.

```
kafka = None
```

The Kafka client

```
kafka_producer = None
```

The Kafka producer

```
kafka_topic = None
```

The Kafka topic we publish to

```
last_connect_attempt = None
```

Remember when the last connection attempt was for reconnect rate-limiting

```
worker_init ()
```

Initialise the Kafka client in each worker

Submodules

`dhcpkit_kafka.server_extension.config` module

Configuration elements for the SOL_MAX_RT option handlers

```
class dhcpkit_kafka.server_extension.config.KafkaHandlerFactory(section:  
                                         ZCon-  
                                         fig.matcher.SectionValue)
```

Bases: `dhcpkit.ipv6.server.handlers.HandlerFactory`

Create the handler for the Kafka producer.

```
create() → dhcpkit_kafka.server_extension.KafkaHandler
```

Create a handler of this class based on the configuration in the config section.

Returns A handler object

```
dhcpkit_kafka.server_extension.config.topic_name(value: str) → str
```

Data validation for Kafka topic names.

Parameters `value` – The value from the configuration file

Returns The validated value

`dhcpkit_kafka.tests` package

Subpackages

`dhcpkit_kafka.tests.messages` package

Submodules

`dhcpkit_kafka.tests.messages.test_dhcp_kafka_message` module

Test the UnknownKafkaMessage implementation

```
class dhcpkit_kafka.tests.messages.test_dhcp_kafka_message.DHCPKafkaMessageTestCase(metho
```

Bases: `dhcpkit_kafka.tests.messages.test_kafka_message.KafkaMessageTestCase` (page 8)

```
parse_packet()
```

```
setUp()
```

Hook method for setting up the test fixture before exercising it.

```
test_load_wrong_type()
```

```
test_validate_message_in()
```

```
test_validate_message_out()
```

```
test_validate_server_name()
```

```
test_validate_timestamp_in()
```

```
test_validate_timestamp_out()
```

```
class dhcpkit_kafka.tests.messages.test_dhcp_kafka_message.NoInboundMessageDHCPKafkaMess
```

Bases: `dhcpkit_kafka.tests.messages.test_kafka_message.KafkaMessageTestCase` (page 8)

```
parse_packet()
```

`setUp()`

Hook method for setting up the test fixture before exercising it.

```
class dhcpkit_kafka.tests.messages.test_dhcp_kafka_message.NoOutboundMessageDHCPKafkaMessage
Bases: dhcpkit_kafka.tests.messages.test_kafka_message.KafkaMessageTestCase (page 8)
```

`parse_packet()`

`setUp()`

Hook method for setting up the test fixture before exercising it.

`dhcpkit_kafka.tests.messages.test_kafka_message` module

Test the KafkaMessage implementation

```
class dhcpkit_kafka.tests.messages.test_kafka_message.KafkaMessageTestCase (methodName='run')
Bases: unittest.case.TestCase

check_unsigned_integer_property (property_name: str, size: int = None)
    Perform basic verification of validation of an unsigned integer
```

Parameters

- `property_name` – The property under test
- `size` – The number of bits of this integer field

`parse_packet()`

`setUp()`

Hook method for setting up the test fixture before exercising it.

`test_length()`

`test_parse()`

`test_save_fixture()`

`test_save_parsed()`

`test_validate()`

`dhcpkit_kafka.tests.messages.test_unknown_kafka_message` module

Test the UnknownKafkaMessage implementation

```
class dhcpkit_kafka.tests.messages.test_unknown_kafka_message.UnknownKafkaMessageTestCase
Bases: dhcpkit_kafka.tests.messages.test_kafka_message.KafkaMessageTestCase (page 8)

parse_packet()
setUp()
    Hook method for setting up the test fixture before exercising it.
test_validate_data()
test_validate_message_type()
```

2.2.2 Submodules

`dhcpkit_kafka.message_registry` module

The option registry

class dhcpkit_kafka.message_registry.KafkaMessageRegistry

Bases: dhcpkit.registry.Registry

Registry for DHCPKit IPv6 Options

entry_point = 'dhcpkit_kafka.messages'**get_name**(item: object) → str

Get the name for the by_name mapping.

Parameters **item** – The item to determine the name of**Returns** The name to use as key in the mapping**dhcpkit_kafka.messages module**

Messages that are sent over Kafka

class dhcpkit_kafka.messages.DHCPKafkaMessage(*server_name*: str = "", *timestamp_in*: Union[int, float] = 0, *message_in*: dhcpkit.ipv6.messages.Message = None, *timestamp_out*: Union[int, float] = 0, *message_out*: dhcpkit.ipv6.messages.Message = None)Bases: *dhcpkit_kafka.messages.KafkaMessage* (page 10)

A message for publishing DHCPv6 messages over Kafka for analysis.

0	1	2	3
0 1 2 3 4 5 6 7 8 9 0	1 2 3 4 5 6 7 8 9 0	1 2 3 4 5 6 7 8 9 0	1
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+	+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+	+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+	
msg-type name-len			.
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+	.	.	.
.	server-name (variable length)	.	.
.	.	.	.
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+	.	.	.
timestamp-in	.	.	.
(double float)	.	.	.
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+	.	.	.
.	.	.	.
.	message-in	.	.
.	(variable length)	.	.
.	.	.	.
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+	.	.	.
timestamp-out	.	.	.
(double float)	.	.	.
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+	.	.	.
.	.	.	.
.	message-out	.	.
.	(variable length)	.	.
.	.	.	.
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+	.	.	.

load_from(buffer: bytes, offset: int = 0, length: int = None) → int

Load the internal state of this object from the given buffer.

Parameters

- **buffer** – The buffer to read data from
- **offset** – The offset in the buffer where to start reading

- **length** – The amount of data we are allowed to read from the buffer

Returns The number of bytes used from the buffer

message_type = 1

save () → Union[bytes, bytearray]

Save the internal state of this object as a buffer.

Returns The buffer with the data from this element

validate ()

Validate that the contents of this object

class dhcpkit_kafka.messages.KafkaMessage

Bases: dhcpkit.protocol_element.ProtocolElement

The base class for Kafka messages.

classmethod **determine_class** (buffer: bytes, offset: int = 0) → type

Return the appropriate subclass from the registry, or UnknownClientServerMessage if no subclass is registered.

Parameters

- **buffer** – The buffer to read data from
- **offset** – The offset in the buffer where to start reading

Returns The best known class for this message data

message_type = 0

class dhcpkit_kafka.messages.UnknownKafkaMessage (message_type: int = 0, mes-

sage_data: bytes = b”)

Bases: [dhcpkit_kafka.messages.KafkaMessage](#) (page 10)

Container for raw message content for cases where we don't know how to decode the message.

load_from (buffer: bytes, offset: int = 0, length: int = None) → int

Load the internal state of this object from the given buffer. The buffer may contain more data after the structured element is parsed. This data is ignored.

Parameters

- **buffer** – The buffer to read data from
- **offset** – The offset in the buffer where to start reading
- **length** – The amount of data we are allowed to read from the buffer

Returns The number of bytes used from the buffer

save () → Union[bytes, bytearray]

Save the internal state of this object as a buffer.

Returns The buffer with the data from this element

validate ()

Validate that the contents of this object conform to protocol specs.

2.3 Changes per version

2.3.1 1.0.0 - 2016-12-08

Fixes

- Limit the queue sizes of pykafka to prevent memory problems when the Kafka cluster is unreachable

Changes for users

- Include documentation

2.4 Applicable copyright licences

2.4.1 DHCPKit License

Copyright (c) 2015-2016, S.J.M. Steffann

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see <<http://www.gnu.org/licenses/>>.

Python Module Index

d

```
dhcpkit_kafka, 6
dhcpkit_kafka.message_registry, 8
dhcpkit_kafka.messages, 9
dhcpkit_kafka.server_extension, 6
dhcpkit_kafka.server_extension.config,
    7
dhcpkit_kafka.tests, 7
dhcpkit_kafka.tests.messages, 7
dhcpkit_kafka.tests.messages.test_dhcp_kafka_message,
    7
dhcpkit_kafka.tests.messages.test_kafka_message,
    8
dhcpkit_kafka.tests.messages.test_unknown_kafka_message,
    8
```

Index

A

analyse_post() (dhcp-
kit_kafka.server_extension.KafkaHandler
method), 6
analyse_pre() (dhcp-
kit_kafka.server_extension.KafkaHandler
method), 6

C

check_unsigned_integer_property()
(dhcpkit_kafka.tests.messages.test_kafka_message.KafkaMessageTestCase
method), 8
connect() (dhcpkit_kafka.server_extension.KafkaHandler
method), 6
create() (dhcpkit_kafka.server_extension.config.KafkaHandlerFactory.kit_kafka.server_extension.KafkaHandler
attribute), 6

D

determine_class() (dhcp-
kit_kafka.messages.KafkaMessage
method), 10
DHCPKafkaMessage (class in dhcp-
kit_kafka.messages), 9
DHCPKafkaMessageTestCase (class in dhcp-
kit_kafka.tests.messages.test_dhcp_kafka_message),
7

dhcpkit_kafka (module), 6

dhcpkit_kafka.message_registry (module),
8

dhcpkit_kafka.messages (module), 9

dhcpkit_kafka.server_extension (module),
6

dhcpkit_kafka.server_extension.config
(module), 7

dhcpkit_kafka.tests (module), 7

dhcpkit_kafka.tests.messages (module), 7
dhcpkit_kafka.tests.messages.test_dhcp_kafka_message
(module), 7

dhcpkit_kafka.tests.messages.test_kafka_message
(module), 8

dhcpkit_kafka.tests.messages.test_unknown_kafka_message
(module), 8

E

entry_point (dhcp-
kit_kafka.message_registry.KafkaMessageRegistry
attribute), 9

G

get_name() (dhcp-
kit_kafka.message_registry.KafkaMessageRegistry
method), 9

K

Kafka (dhcpkit_kafka.server_extension.KafkaHandler
attribute), 6
kafka_producer (dhcp-
kit_kafka.server_extension.KafkaHandler
attribute), 6

kafka_topic (dhcp-
kit_kafka.server_extension.KafkaHandler
attribute), 6

KafkaHandler (class in dhcp-
kit_kafka.server_extension), 6
KafkaHandlerFactory (class in dhcp-
kit_kafka.server_extension.config), 7

KafkaMessage (class in dhcpkit_kafka.messages),
10
KafkaMessageRegistry (class in dhcp-
kit_kafka.message_registry), 8

KafkaMessageTestCase (class in dhcp-
kit_kafka.tests.messages.test_kafka_message),
8

L

last_connect_attempt (dhcp-
kit_kafka.server_extension.KafkaHandler
attribute), 6
load_from() (dhcp-
kit_kafka.messages.DHCPKafkaMessage
method), 9

load_from() (dhcp-
kit_kafka.messages.UnknownKafkaMessage
method), 10

M

message_type (dhcp-

